DECLARATION OF PERFORMANCE (DOP)

	NO. 91004604 CPR-20200303	
1.	Product Type:	Freestanding stove Scan 1004-B Ceramic stone
2.	Type, batch or serial number:	Scan 1004-B CS
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Damsbovej 1 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body: Test report no:	DTI NB-No 1235 300-ELAB-2382-EN REV. 2 300-ELAB-2184-EN SIK-REV. 3
8.	Declared performance	
	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics	Performance
	Fire safetyReaction to fireDistance to combustible materials	A1 Minimum distances in mm: Rear: 150
	Risk of burning fuel falling out	Sides: 500 Front: 1500 No
	Risk of burning fuel falling out Emission of combustion products	Front: 1500
		Front: 1500 No CO [1148 mg/Nm ³] NOx [95 mg/Nm ³] OGC [45 mg/Nm ³]
	Emission of combustion products	Front: 1500 No CO [1148 mg/Nm ³] NOx [95 mg/Nm ³] OGC [45 mg/Nm ³] Staub [29 mg/Nm ³]
	Emission of combustion products Surface temperature	Front: 1500 No CO [1148 mg/Nm ³] NOx [95 mg/Nm ³] OGC [45 mg/Nm ³] Staub [29 mg/Nm ³]
	Emission of combustion products Surface temperature Electrical safety	Front: 1500 No CO [1148 mg/Nm ³] NOx [95 mg/Nm ³] OGC [45 mg/Nm ³] Staub [29 mg/Nm ³] Pass -
	Emission of combustion products Surface temperature Electrical safety Cleanability	Front: 1500 No CO [1148 mg/Nm ³] NOx [95 mg/Nm ³] OGC [45 mg/Nm ³] Staub [29 mg/Nm ³] Pass - Pass
	Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure	Front: 1500 No
	Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure Flue gas temperature at nominal heat output [EN]	Front: 1500 No CO [1148 mg/Nm³] NOx [95 mg/Nm³] OGC [45 mg/Nm³] Staub [29 mg/Nm³] Pass - Pass - T [242°C]

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Brian Steen Ørum (Senior Project Manager)

Vissenbjerg, 03.03.2020

(Place and date of issue)

SCA

Brin Jun . (Signatute)