



DECLARATION OF PERFORMANCE

NO. 90179601-CPR-20260704	
1. Unique identification code of the product type	Scan 79 Zensoric
2. Intended use(s)	Space heating in residential buildings
3. Manufacturer / trade mark	Jøtul AS Postboks 1411 1602 Fredrikstad, Norway
4. Authorised representative	-
5. System(s) of assessment and verification of constancy of performance of the construction product	System 3
6. The notified test laboratory has performed the initial test according to system 3 Notified body	NB No 1235 (DTI) 300-ELAB-2727-EN
7. Harmonised technical specifications	EN 16510-1:2022, EN 16510-2-1:2022
8. Essential characteristics	
Mechanical resistance and stability	
Load bearing capacity	120 kg
Safety in case of fire	
Minimum distance to combustible materials - below the bottom (not regarding feet)	$d_B = 0$ mm
Minimum distance to combustible materials - front to the bottom front radiation area	$d_F = 0$ mm
Minimum distance to combustible materials - ceiling	$d_C = 750$ mm
Minimum distance to combustible materials - rear	$d_R = 200^*$ mm
Minimum distance to combustible materials - side	$d_S = 450$ mm
Minimum distance to combustible materials - front to the side front radiation area	$d_L = 0$ mm
Minimum distance to adjacent combustible materials (e.g. furniture)	$d_P = 1050$ mm
Hygiene, health and environment	
Emissions at nominal heat output	
Carbon monoxide emission (CO)	522 mg/Nm ³
Nitrogen oxides emission (NO _x)	88 mg/Nm ³
Emission of organic gaseous carbon (OGC)	35 mg/Nm ³
Particulate matter emissions (PM)	13 mg/Nm ³
Emissions at part load heat output	
Carbon monoxide emission (CO)	1499 mg/Nm ³
Nitrogen oxides emission (NO _x)	99 mg/Nm ³
Emission of organic gaseous carbon (OGC)	76 mg/Nm ³
Particulate matter emissions (PM)	14 mg/Nm ³


*See manual for distance to insulated flue pipe



DECLARATION OF PERFORMANCE

Safety and accessibility in use		
Data for installation to a chimney at nominal heat output		
Flue gas outlet temperature	338 °C	
Minimum flue draught	12 Pa	
Flue gas mass flow	4.8 g/s	
Data for installation to a chimney at part load heat output		
Flue gas outlet temperature	310 °C	
Minimum flue draught	6 Pa	
Flue gas mass flow	4.2 g/s	
Data for installation to a chimney regarding fire safety on safety test heat output		
Fire safety of installation to the chimney	T400 G	
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at nominal heat output		
Space heat output	5.8 kW	
Water heat output (if available)	NPD	
Efficiency	81 %	
Appliance's thermal output and energy efficiency at part load heat output		
Space heat output	4.2 kW	
Water heat output (if available)	NPD	
Efficiency	79 %	
Space heating efficiency		
Seasonal space heating efficiency at nominal heat output	71 %	
Energy Efficiency	Energy Efficiency Index (EEI)	107
	Energy Efficiency Class	A+
Electric power consumption at appliance's nominal heat output (if available)	NPD	
Electric power consumption at appliance's part load heat output (if available)	NPD	
Power consumption in standby mode (if available)	NPD	
Sustainable use of natural resources		
Environmental sustainability	NPD	
9.	The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.	

„NPD“ (No Performance Determined), if no quality is stated

Signed on behalf of the manufacturer	
Place and date of issue	Fredrikstad, Norway 07.04.2026
 Lena Bergqvist (COO)	
