## DECLARATION OF PERFORMANCE (DOP)

	NO. 91010600-CPR-20160907	
1.	Product Type:	Freestanding stove Scan 1010
2.	Type, batch or serial number:	Scan 1010-series
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Glassvænget 3-9 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body: Test report no:	DTI NB-No 1235 300-ELAB-1588-EN/ 300-ELAB-2184-EN
8.	Declared performance	
	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics	Performance
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1400 NPD
	Emission of combustion products	CO [0,1 %] NOx [41 mg/Nm <sup>3</sup> ] OGC [29 mg/Nm <sup>3</sup> ] Dust [12 mg/Nm <sup>3</sup> ]
	Surface temperature	Pass
	Electrical safety	-
	Cleanability	Pass
	Maximum water operating pressure	-
	Flue gas temperature at nominal heat output [EN]	T [220°C]
	Mechanical resistance (to carry a chimney/flue)	NPD
	Thermal outputNormal heat outputRoom heating outputWater heating output	7 kW
	Energy efficiency	ŋ [82 %]

## DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Ole Hansen (R&D LAB)

Vissenbjerg, 01.09.2016

(Place and date of issue)

SCNN

Ou Ham

(Signatute)

## DECLARATION OF PERFORMANCE (DOP)

	NO. 91010601-CPR-20160907	
1.	Product Type:	Wall mounted stove SCAN 1010
2.	Type, batch or serial number:	Scan 1010-series
З.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Glassvænget 3-9 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body: Test report no:	DTI NB-No 1235 300-ELAB-1588-EN/ 300-ELAB-2184-EN
8.	Declared performance	
	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics	Performance
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Sides: 500 Front: 1400 Floor: 400 NPD
	Emission of combustion products	CO [0,1 %] NOx [41 mg/Nm <sup>3</sup> ] OGC [29 mg/Nm <sup>3</sup> ] Dust [12 mg/Nm <sup>3</sup> ]
	Surface temperature	Pass
	Electrical safety	-
	Cleanability	Pass
	Maximum water operating pressure	-
	Flue gas temperature at nominal heat output [EN]	T [220°C]
	Mechanical resistance (to carry a chimney/flue)	NPD
	Thermal outputNormal heat outputRoom heating outputWater heating output	7 kW - -
	Energy efficiency	ŋ [82 %]

## DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Ole Hansen (R&D LAB)

Vissenbjerg, 01.09.2016

(Place and date of issue)

SCNN

Ou Ham

(Signatute)