At nominal heat output	Model identifier(s): Scan 1004-B CS										
Indirect heat output(kW)	Indirect heating functionality				No						
Fiel Preferred fol (Only one) Identifier(s) PM OGC CO NO₂	Direct heat output(kW)				8						
Preferred fuel Pre	Indirect heat output(kW)				N.A						
Freier found (Only one) identifier(s) [Simply-In (13 % O)] Wood logs with moisture content < 25% Yes No 29 \$5 1242 94 Compressed wood with moisture content < 12% No No No 29 \$5 1242 94 Compressed wood with moisture content < 12% No											
Wood logs with moisture content < 25% Yes No 29 55 1242 94										NO _x	
Compressed wood with moisture content < 12% No	Fuel						[X] mg/Nr	n ₃ (13 % C) ₂)		
Other woody biomass No N	Wood logs with moisture content ← 25%				Yes	No	29	55	1242	94	
Anthracite and dry steam coal Hard coke No No No Hard coke No Highligh briquettes No No No Ho No Heat prigettes No No No Ho Ho Heat prigettes Heat prigettes No No No Ho Ho Heat prigettes Heat prigettes No No No Ho Ho Heat prigettes Heat prigettes Heat prigettes No No No Ho Ho Ho Heat prigettes					No	No					
Hard coke Low temperature coke No No No Lignite briquettes No No No Lignite briquettes No No No Blended fossil fuel briquettes No No No Other fossil fuel briquettes No No No Other fossil fuel briquettes No No No Other blend of biomass and solid fuel Characteristics when operating with the preferred fuel Seasonal space heating energy efficiency n _c [%] Energy Efficiency Class Energy Efficiency Index (EEI) Item Symbol Value Unit Heat output Nominal heat output (Indicative) Auxiliary electricity consumption At nominal heat output At minimum heat output In standby mode el. xxxxx kW In standby mode el. xxxxx kW Name and address of the supplier:	·				No	No					
Description of the proper state of the supplier: No No No No No No No N	•				No	No					
Bituminous coal Lignite briquettes No No No No Peat briquettes No No No No No Peat briquettes No No No No No No Peat briquettes No N	Hard coke				No	No					
Lignite briquettes	Low temperature coke				No	No					
Peat briquettes No No No No No No No N	·				No	No					
Blended fossil fuel briquettes Other fossil fuel Blended biomass and fossil fuel briquettes No N	Lignite briquettes				No	No					
Other fossil fuel Blended biomass and fossil fuel briquettes No No No No Other blend of biomass and solid fuel No					No	No					
Blended biomass and fossif fuel briquettes Other blend of biomass and solid fuel No N	Blended fossil fuel briquettes				No	No					
Other blend of biomass and solid fuel Characteristics when operating with the preferred fuel Seasonal space heating energy efficiency n ₁ [%] Energy Efficiency Index (EEI) Item Symbol Value Unit Heat output Nominal heat output P sum 8 kW Minimum heat output P sum N.A. kW Minimum heat output el sum x.xxxx kW At mominal heat output el sum x.xxxx kW At minimum heat output el sum x.xxxx kW In standby mode el sum x.xxxxx kW In stand	Other fossil fuel				No	No					
Characteristics when operating with the preferred fuel Seasonal space heating energy efficiency \(\text{\(\)_{\text{\(\)_{\indth}\(\)_{\text{\(\)_{\t	Blended biomass and fossil fuel briquettes				No	No					
Seasonal space heating energy efficiency \(\pi_{\text{lengy}} \)	Other blend of biomass and solid fuel				No	No					
Energy Efficiency Class Energy Efficiency Index (EEI) Item Symbol Value Unit Heat output Nominal heat output P _{nom} 8 kW Minimum heat output (indicative) P _{min} N.A. kW Minimum heat output (el _{max} x.xxx kW At nominal heat output el _{max} x.xxx kW At minimum heat output el _{max} x.xxx kW In standby mode el _{ss} x.xxx kW In s	Characteristics when operating with the preferred fuel										
Item Symbol Value Unit Item Symbol Value Unit Use efficiency (NCV as received)											
Item Symbol Value Unit Item Symbol Value Unit Heat output	Energy Efficiency Class		-		A +						
Use efficiency (NCV as received)	Energy Efficiency Index (E	108									
Use efficiency (NCV as received)	Item	Symbol	Value	Unit	It	Symbol	mbol Value		Unit		
Nominal heat output P_nom 8 kW Useful efficiency at nominal heat output N.A. W Useful efficiency at minimum heat output N.A. W Useful efficiency at minimum heat output N.A. W Useful efficiency at minimum heat output N.A. W W Useful efficiency at minimum heat output N.A. W W W W W W W W W	Heat output	,			Use efficiency (NCV as re		ceived)				
Maxiliary electricity consumption At nominal heat output elmax x,xxx kW two or more manual stages, no room temperature control with mechanic thermostat room temperature control with electronic room temperature control plus day timer With electronic room temperature control with electronic room temperature control plus week timer Other control options (multiple selections possible) room temperature control, with presence detection power requirement Pilot flame power requirement Pilot flame power requirement (if applicable) P pilot N.A. KW Name and address of the supplier: Amail output (indicative) Type of heat output (indicative) Type of heat output (indicative) Type of heat output, no room temperature control (select one single stage heat output, no room temperature control [yes/no] Type of heat output, no room temperature control [yes/no] With electronic room temperature control [yes/no] With electronic room temperature [yes/no] Other control options (multiple selections possible) Tope of heat output, no room temperature control [yes/no] With mechanic thermostat room [yes/no] With electronic room temperature [yes/no] Other control options (multiple selections possible) Tope of heat output, no room [yes/no] With electronic room temperature [yes/no] Other control options (multiple selections possible) Tope of heat output, no room [yes/no] With electronic room temperature [yes/no] Other control options (multiple selections possible) Tope of heat output, no room [yes/no] Other control options (multiple selections possible) Tope of heat output, no room [yes/no] Tope of heat output, no room [yes/no] With electronic room temperature [yes/no] Tope of heat output, no room [yes/no	·	P _{nom}	8	kW				m 81		%	
At nominal heat output el max x.xxx kW single stage heat output, no room temperature control [yes/no] Yes At minimum heat output el min x.xxx kW two or more manual stages, no room temperature control [yes/no] Yes In standby mode el sa x.xxx kW two or more manual stages, no room temperature control [yes/no] with mechanic thermostat room temperature control [yes/no] with electronic room temperature [yes/no] other control options (multiple selections possible) room temperature control, with [yes/no] room temperature control, with [yes/no] permanent pilot flame power requirement N.A. kW Name and address of the supplier:	Minimum heat output (indicative)	P _{min}	N.A.	kW	minimum he	eat	η _{th, min}	N.A.		%	
At nominal heat output	Auxiliary electricity con		Type of heat output/room temperature control (select one								
In standby mode el_{SB}			x,xxx	kW	single stage	e heat output, i	no room [yes/no]			,	
temperature control with electronic room temperature control plus day timer with electronic room temperature control plus week timer Other control plus week timer Other control, with presence detection room temperature control, with presence detection room temperature control, with open window detection with distance control options (multiple selections possible) room temperature control, with open window detection with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement (if applicable) Name and address of the supplier: Amr. Au.	At minimum heat output	el _{min}	x,xxx	kW	two or more	two or more manual stages, no room temperature control [yes,				Yes	
control with electronic room temperature control plus day timer with electronic room temperature control plus week timer Other control options (multiple selections possible) room temperature control, with presence detection room temperature control, with open window detection permanent pilot flame power requirement Pilot flame power requirement (if applicable) Name and address of the supplier: Amage days timer [yes/no] with electronic room temperature control options (multiple selections possible) room temperature control, with open window detection with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement (if applicable) Name and address of the supplier:	In standby mode	el _{sB}	x,xxx	kW					no]		
control plus day timer with electronic room temperature control plus week timer Other control options (multiple selections possible) room temperature control, with presence detection room temperature control, with open window detection room temperature control, with open window detection with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement Name and address of the supplier:						oerature	[yes/no]				
Control plus week timer Other control options (multiple selections possible) room temperature control, with presence detection room temperature control, with open window detection with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement (if applicable) Name and address of the supplier:					with electro control plus	perature	[yes/no]				
room temperature control, with presence detection room temperature control, with open window detection permanent pilot flame power requirement Pilot flame power requirement (if applicable) Name and address of the supplier:					with electro control plus	perature	[yes/no]				
presence detection [yes/no] room temperature control, with open window detection [yes/no] with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement (if applicable) P pilot N.A. kW Name and address of the supplier:					Other cont	ultiple sele	ctions pos	ssible)			
Permanent pilot flame power requirement Pilot flame power requirement (if applicable) Name and address of the supplier:					room tempo presence do	room temperature control, v presence detection			no]		
Permanent pilot flame power requirement Pilot flame power requirement (if applicable) Ppilot N.A. kW Name and address of the supplier:					room tempo open windo	erature contro w detection	l, with				
Pilot flame power requirement (if applicable) P _{pilot} N.A. kW Name and address of the supplier:					with distan	ce control opti	on	[yes/	no]		
requirement (if applicable) Name and address of the supplier:			ement								
Mar blow	requirement (if applicable)	-					, //	1			
Contact details Brian Ørum, R&D Manager, Scan A/S, Denmark	Contact details	Name and a	address of th	ne supplier:		Brian Ørum, R&I) Manager, Sca	, n A/S, Denma	ırk		