Model identifier(s): Scar	n 66								
Indirect heating functionality				No					
Direct heat output(kW)				5					
Indirect heat output(kW)				N.A					
					Emissions from space heating at nominal heat output				
				Preferred			OGC	CO	NO <sub>x</sub>
Fuel				<b>fue</b> l (Only one)	Model identifier(s)	[X] mg/Nr			IIO <sub>X</sub>
Wood logs with moisture content ← 25%				Yes	No	27	34	428	86
Compressed wood with moisture content < 12%				No	No			0	30
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when op									
Seasonal space heating er	<u> </u>	•		68					
Energy Efficiency Class				А					
Energy Efficiency Index (E	103								
Item	Symbol	Value	Unit	It.	Symbol Value		lue	Unit	
Heat output				<b>Use efficiency</b> (NCV as re					
Nominal heat output	$P_{nom}$	5	kW	Useful efficiency at nominal heat output		η <sub>th, nom</sub> 78		8	%
Minimum heat output (indicative)	P <sub>min</sub>	N.A.	kW	Useful effic minimum he output (ind	$\eta_{\text{th, min}}$	N.A.		%	
Auxiliary electricity cons	Type of heat output/room temperature control (select one)								
At nominal heat output	el <sub>max</sub>	x,xxx	kW	single stag temperatur	· · · · · · · · · · · · · · · · · · ·				
At minimum heat output	el <sub>min</sub>	x,xxx	kW	two or more	es, no l	s, no [yes/		Yes	
In standby mode	el <sub>sB</sub>	X,XXX	kW	with mecha temperatur	t room	[yes	/no]		
				with electro	perature	re [yes/no]			
				with electro control plus	perature [yes/no]		/no]		
				with electro control plus	perature	[yes/no]			
				Other cont	nultiple sele	ections po	ossible)		
				room temp presence d	l, with	[yes	/no]		
				room temp open windo		vith [yes/no]			
			with distance control option			[yes	/no]		
Permanent pilot flame p									
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	N.A.	kW				1		
Name and address of the supplier:  Contact details  Brian Ørum, R&D Manager, Scan A/S, Denmark									